

Departament tehnic

6 0743 114 113 C Program Luni-Vineri: 14:00-18:00

Manual de utilizare

Termostat inteligent pentru centrala termica pe gaz si incalzire in pardoseala

Beok TR9B-WIFI-WPB



1. Descriere produs

Termostatul Wi-Fi BeOK TR9B-WIFI-WPB poate fi utilizat direct prin interfata tactila (touchscreen) sau poti controla temperatura si functiile termostatului de pe smartphone cu ajutorul aplicatiei "Smart Life" disponibila in Google Play / App Store.

2. Parametrii tehnici

Tensiune lucru	AC100~240V; 50~60Hz
Consum	1W max. (Wi-Fi 3W max.)
Dimensiune	86 x 86 x ~50 mm
Material	PC (ignifug)
Setare temperatura de functionare	5°C - 95°C
Interval temperatura incalzire	20°C - 90°C
Acuratete	±1°C

3. Caracteristici si functii principale

O) Case-Smart[®]

Conexiune Wi-Fi pentru smartphone-uri Android si iOS.

Afisaj cu ecran mare si butoane tactile.

Functie de memorare: Iti va memora setarile, astfel in caz de pana de curent, nu va mai trebui sa il resetezi.

Functie de salvare a datelor in timp real.

Termostatul este programabil cu 6 intervale orare pe zi.

Protectie impotriva temperaturilor scazute!

3 moduri de control temperatura (auto, manual, temporar).

Functie de blocare termostat, astfel incat copii tai sa nu umble la el!

4. Interfata utilizator (termostat)



5. Mod control temperatura

Mod auto

Programari saptamanale, pana la 6 intervale orare pe zi.

地 Mod manual

Termostatul functioneaza si in modul manual, ajustand temperatura manual, deconectandu-se astfel de la modul auto.

b Mod temporar

Termostatul functioneaza in modul temporar si apoi se schimba inapoi in modul auto pana la urmatorul eveniment.

6. Diagrama de instalare



(1) Deschide panoul usor cu o surubelnita!



(2) Conecteaza firele de alimentare conform schitei de cablare! Foloseste doua suruburi pentru a fixa suportul.



(3) Acopera panoul tactil.



(4) Apasa butonul Opentru a porni termostatul.

7. Diagrama de cablare TR9B-WIFI-WPB



8. Instructiuni butoane termostat

ON/OFF

Apasa 🖒 pentru a deschide/inchide termostatul.

Modul auto

Apasa M timp de 3 secunde pentru a edita modul auto.

Setare perioada

Apasa 🥔 timp de 3 secunde pentru a seta perioada.

Setare temperatura

Apasa ▲ sau ✔ pentru a schimba temperatura cu 0.5 °C.

Protectie copii

Apasa \land + \checkmark timp de 3 secunde pentru a activa aceasta functie.

Control temperatura

Apasa M scurt pentru a schimba modurile manual/auto.

Modul Eco

Apasa 🥔 scurt pentru a seta modul ECO 18°C.

9. Setari mod auto

Apasa M timp de 3 secunde pentru a edita modul auto.

Eveniment		Simbol	Tim	р	Temperatura		
		SIMDOI	Implicit	Modificat	Implicit	Modificat	
	1	÷.	06:00		20 °C (68 °F)		
	2	<u> </u>	08:00	Δηρερ	15 °C (59 °F)	Apasa	
Zile	3	X •	11:30		15 °C (59 °F)		
saptamana	4	80	12:30	▲	15 °C (59 °F)		
	5	۵	17:00	sau	22 °C (72 °F)	sau	
	6	Q	22:00		15 °C (59 °F)		
Wookond	1	¢	06:00		20 °C (68 °F)		
VVEEKEIIU	2	D	20:00		20 °C (68 °F)		

10. Ghid de instalare aplicatie mobila Smart Life

- Deschideti mai intai aplicatia "Smart Life" si creati-va un cont.
- Introduceti adresa dvs. de e-mail pentru a primi un cod de verificare.
- Introduceti codul de 6 cifre si apoi setati o parola.



Pasul 1 - Logati-va cu datele de inregistrare ale contului creat



Pentru a conecta termostatul la aplicatia "Smart Life", aceasta trebuie mai intai descarcata prin scanarea **codului OR**.

Pasul 2 - Modul Bluetooth

Activati mai intai Bluetooth-ul pe telefon.

0.001 (30 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	<	orange عند "بط الله الله الله الله الله الله الله الل	3日本中ローロー12:05 Scan こう (8LE)	orange 100 * # 完 @ -	orange 🚍 ".ifi 😤 🌚 Cancel	வை≉மை இப்பாக Bluetooth ⇔	oronge 📼 🖬 🕯	完め 品質参印(部):1206
How to add devices in the App? Add Device Top + to add a smart device.	Electrical Lighting Sensors	Mover (M-Fi)	Robet Vocuum r (IPC)	Select 2.4 GHz Wi-Fi Network and enter password. If your Wi-Fi is 50Hz, please set it to be 2.4GHz. Common router setting method	Reset the device first. Power on the device and confir indicator is blinking rapidly. Note: please complete the netu distribution within 3 minutes aft device.	m that the work ter resetting the	Adding Ensure that the de	device
Opriti termostatulsi tineti	Large Home Appliances Small Home Appliances Kitchen Appliances Exercise & Health	Remotat (R4 VH-F) Demotat (R5) Demotat (R5) Verification System (R1 + VH-F) (R1 + VH-F) (R	on Ventilation FFI Ventilation	x WrFi- 2.46hz + ♥ ①	Perform net poiring as p	rompted. >		:57
	Security & Video Sur Gatewoy Control Outdoor Travel Energy	Ventificion System (Zigbee) TRV Moto	HWAC (Wi-Fi)	Net	Confirm the indicator rapidly. Next	is blinking	Scan Regi devices. Cl	c
			\triangleleft			\triangleleft		

- Faceti click pe iconita 😛 pentru a adauga dispozitivul.
- Cautati "Small Home Appliances" si apoi selectati "Thermostat (BLE+Wi-Fi)".
- Conectati-va la reteaua Wi-Fi 2.4 Ghz si apoi confirmati faptul ca indicatorul clipeste.
- Asteptati ca dispozitivul sa fie adaugat.

Pasul 3 - Modul AP

conge 國 #J 使 使 回 1200	orange 🕮 ්යේ 😤 ම 🛛 🖬 ම 🖓 🕮 12:05	orange 2011년 18년 19년 19년 19년 19년 19년 19년 19년 19년 19년 19	orange 🖾 ්යේ 😤 ම 🛛 🛱 ම 🛈 🕮 1217	orange 🖾 ".네 영 🐵 🎧 🗃 8 🖓 🕮 12.08	ourge 🕮 "යේ 🔍 ම 🛛 🛱 මාට 🕮 12.06
	Add Manually Auto Scan	Cancel	Cancel AP Mode =	Cancel	Cancel
How to add devices in the App? Add Device Top + to add a unrent device.	Lapton Karr Karr Karr Karr Karr Karr Karr Kar	Select 2.4 GHz Wi-Fi Network and enter password. If your Wi-Fi is Solit, please at it to be 2.40kt. Common rooter setting method	Reset the device first. Proze power on the device and confirm that the indicator is binking slowly. Note: pieces complete the network distribution within 3 minutes after resetting the device.	Connect your mobile phone to the device's hotspot	Adding device Ensure that the device is powered on.
Opriti termostatul si tineti lung apasat pe	Operating Sector Operating Sector<	▼ WiFi 2.40hz * ▼ ①	Perform net pairing as prompted. >	Standarder Weight Standarder Weight Standarder Weight Standarder Weight Standarder Weight Standarder Weight	01:57
	Ostaney Colater Ostaner Terrery Frenzy Mator		Confirm the indicator is blinking slowly.	Go to Connect	Scan Register on Holdsate the devices. Befores. Cloud. device.

- Faceti click pe iconita 😛 pentru a adauga dispozitivul.
- Cautati "Small Home Appliances" si apoi selectati "Thermostat (BLE+Wi-Fi)".
- Conectati-va la reteaua Wi-Fi **2.4 Ghz**, verificati ca modul AP sa fie selectat si apoi confirmati faptul ca indicatorul clipeste.
- Asteptati ca dispozitivul sa fie adaugat.

Pasul 4 - Partajare dispozitiv

معتور ۲۰۰۵ ۲۰۰۵ ۲۰۰۵ ۲۰۰۵ ۲۰۰۵ ۲۰۰۵ ۲۰۰۵ ۲۰۰	Competitive Reserved Automatic Action of the second s	comp: 20 *4 €. 20 €10 162 143 Comp: 20 *4 €. 20 €10 162 143 Comp: 20 *4 €. 20 *40 *40 *40 *40 *40 *40 *40 *40 *40 *4	compre ■ "d ♥. ■ ♥ 0.0 m 14.55 C Decice Sharing resident in your home has an account, we recommend that you set has account as a family member and share all your family devices and "Tap-To- Run" Scene with the family member; lowns Settings	competent of the function
	15.0°C Set Temperature	Device information > Tap-to-Run and Automation > Device Offline Notification Offline Notification		
Apasati pe dispozitiv	18.7° ^C Middle ON Room Fan Cooling	Others Share Device Partajare dispozitiv Create Group > FAQ & Feedback >		Please make sure to connect the dual-mode device to Internet, or the recipient may not be able to control your product. Continue?
	System mode Cooling > System mode Cooling > Fan Middle >	Add to Home Screen > Check Device Network >		Cancel Confirm
	Child Edex Advanced Settings	Device Update >	Apasati pentru partajare dispozitiv	Apasati pentru confirmare
		Remove Device	Add Sharing	Add Sharing

- Apasati pe dispozitiv pentru a accesa setarile acestuia.
- Apasati pentru redenumire dispozitiv.
- Faceti click pe "Share Device" pentru partajare dispozitiv.
- Faceti click pe "Add Sharing" pentru adaugare persoane.
- Apasati **"Confirm"** pentru confirmare.



- Apasati pentru a introduce contul persoanei careia i se partajeaza dispozitivul.
- Partajarea s-a finalizat cu succes.

Pasul 5 - Interfata aplicatiei mobile

